R32 SINGLE/MULTI- ZONE 8-way CASSETTE SYSTEM

9,000 BTU / H CASSETTE

SUBMITTAL DATA: TKH09D32AI + TWH09PD32AO

Job Name	Location		Date	
Purchaser	Engineer			
Submitted To	For	Reference	Approval	Construction
Unit Designation	Schedule No.			

AHRI CERTIFIED REF	**218001423**
ENERGY STAR No.	**4515431**





YBE1FB1F (Standard)



YAW1F9 Cool-only (Optional)



SQZ004 (Optional)



XE72-44/E (Optional)



XE71-00/E (Optional)



SYSTEM RATINGS		INDOOR UNIT DATA	
Cooling		**Fan Motor**	
Rated Capacity @ 95° F	9,100 BTU/H	Type	Centrifugal
Capacity Range	2,560-11,900 BTU/H	Panel Dimension W x L x H (inch)	24-13/32x 24-13/32x 1-7/8
Power Input	610 W	Output Power	30 W
Power Input (Min/Max)	150 / 890 W	FLA	0.5 A
SEER2 / EER2	24.00 / 15.00	Drainage Hose Size	3/4”
Heating		Air flow (Min/Max)	224/330 CFM
Rated Capacity @ 47° F	10,500 BTU/H	Dehumidification	2.96 pt/hr
Capacity Range	2,900-13,700 BTU/H	**Sound Pressure Level**	
Rated Capacity @ 17°F	8,800 BTU/H	Min / Max	31 / 40 dB(A)
Rated Capacity @ 5°F	7,600 BTU/H	**OUTDOOR UNIT DATA**	
Power Input	800 W	**Compressor**	
Power Input (Min/Max)	160 / 1,100 W	Type	DC Inverter Rotary
HSPF2 (Region IV / V)	9.2 / 7.0	RLA	6.5A
COP @47°F / @5°F	3.85 / 1.94	**Fan Motor**	
Operating Range		Output Power	30 W
Cooling	0°F ~ 122°F	FLA	0.96 A
	-18°C ~ 50°C	Sound Pressure Level	50 dB(A)
Heating	-22°F ~ 86°F	**Refrigerant Piping Data**	
	-30°C ~ 30°C	Liquid Pipe Size (OD)	1/4-in
Power Supply		Gas Pipe Size (OD)	3/8-in
Rated	208/230 V, 1 Phase, 60 Hz	Connection Method	Flared
Voltage Range	187 - 253 V	Pre-Charged R32 Amount	30.0 oz
Main Power Wire Size	Per Local Code	Additional Charge	0.2 oz/ft
Wire Size between IDU & ODU	14-4 AWG	Pre-Charge Length	25-ft
MCA	10 A	MAX Refrigerant Pipe Length	66-ft
MOCP/Max Breaker Size	15 A	MIN Refrigerant Pipe Length	10-ft
Moisture Protection	IPX4	MAX Refrigerant Pipe Height Difference	40-ft

FEATURES & FUNCTION SUMMARY: TKH09D32AI + TWH09PD32AO


SYSTEM FEATURES	
Multi Fan Speeds	7 Speeds
Indoor Fan Type	Centrifugal
Artificial Intelligence for Saving Energy	Version 1.0
Wired Controller Interface	YES
Auxiliary Electrical Heater	NO
Ventilation (Outdoor Air)	YES
Condensate Pump	YES
Overflow Cut-off Switch	YES
Electronic Expansion Valve	In Outdoor Unit
Coil Construction	Copper Tube-Aluminum Fin
Indoor Fin Coating (Blue)	Acrylic Resin/Anti-Corrosion
A2L Refrigerant Leakage Detector	Optional
WIRED CONTROLLER & REMOTE CONTROLLER FUNCTIONS	
Auto Mode	YES
Auto Fan	YES
Turbo Cooling	YES
Auto Swing (Horizontal)	NO
Auto Swing (Vertical)	YES
Dry Mode	YES
Dry Anti-Mildew (X-Fan) Mode	YES
Energy Saving Mode	YES
I Feel Function	YES
Lock on Remote Controller	YES
Quiet Mode	NO
Long Time Room Temperature Display ※	YES
Normal Sleep Mode	YES
Timer Mode	YES
LCD Back Light on Remote Controller	YES
Turbo Mode	YES
Cooling Only Controller	Optional with Remote YAW1F9
Freeze Guard/Holiday Mode (46°F/8°C)	YES
24Vac Signal 3rd party Backup Heater Output	Optional with XE71-00/E, SQZ004
Wifi Control	Optional with XE72-44/E

※ Available on XE72-44/E with [Mode]+[▲] during OFF status


DIMENSIONAL SPECIFICATIONS: TKH09D32AI

INDOOR UNIT DIMENSION

Unit: inch




Dimensions	
A	24 13/32
B	22 53/64
C	22 7/16
D	19 7/8
E	21 21/32
F	10 7/16
G	5 33/64
H	20 55/64
I	20 55/64



Unit Weight (Net/Gross) 38 / 49 LBS
Panel Weight (Net/Gross) 7 / 10 LBS

INDOOR CLEARANCE

Unit: inch




TOSOT.COM


DIMENSIONAL SPECIFICATIONS: TWH09PD32AO

MINIMUM SPACING REQUIREMENTS

Unit: inch




The ceiling should be open





Either left or right side should be open

Note: Wall height on air outlet side ≤ 50inch

OUTDOOR UNIT DIMENSIONS







Unit: inch

Weight (Net/Shipping)
71 / 76 LBS

Liquid Line Valve	1/4-in OD Flared
Gas Line Valve	3/8-in OD Flared

Notes:

1. Recommended Interconnecting Cable Type 14 AWG 4 Stranded Copper Conductors Wire
2. Power wiring cable size must comply with applicable national and local codes
3. Test conditions are based on AHRI 210/240.