TOSOT

TMV- 5 mini Series

36,000 BTU / VRF SYSTEM

SUBMITTAL DATA: TMVRF-OD36KHP

Job Name	Location		Date	
Purchaser	Engineer			
Submitted To	For	☐ Reference	☐ Approval	☐ Construction
Unit Designation	Schedule No.			

TMVRF-OD36KHP



Model			TMVRF-OD36KHP
System Performance			
Capacity Range		Ton	3
Nominal Capacity	Cooling	kBtu/h	37.6
	Heating	kBtu/h	42.0
Sound Pressure Level		dB(A)	55.0
Operating Temperature Range	Cooling	°C/°F	-5~48 / 23~118
	Heating	°C/°F	-20~27 / -4~81
AHRI Certificate Reference Number		-	212117654 / 212117655
Cooling Capacity@95F		kBtu/h	37.4 / 37.4
SEER(Ducted/Non-Ducted)		-	19.50 / 22.00
SEER2(Ducted/Non-Ducted)		-	18.00 / 22.00
Heating Capacity@47F		kBtu/h	42 / 42
HSPF(Ducted/Non-ducted)		-	10.50 / 11.00
HSPF2(Ducted/Non-ducted)		-	8.20 / 9.80
Heating Capacity@5F(Ducted/Non-ducted)		kBtu/h	20.0 / 21.0
Electrical Data			
Power Supply		-	208/230V, 1 Phase, 60Hz
Maximum Overcurrent Protection (MOP)		A	35.0
Minimum Circuit Amps (MCA)		A	28.5
Fan			
Type x Quantity		-	Axial- flow x 2
Air Flow Volume		CFM	3,531
		m^3/h	6,000
Fan Motor Power Output		W	120
Compressor			
Compressor Type x Quantity		-	Inverter rotary x 1
Compressor Rated Load Amps (RLA)		A	19.7
Oil Type		-	FW68DA
Oil Charge Volume(Compressor charged)		L	1
Connection Piping			
Gas Pipe		inch	5/8
Liquid Pipe		inch	3/8
Refrigerant Type		-	R410A
Refrigerant Charge Amount		kg/oz	3.3 / 116.4
Dimension/Weight			
Unit Dimensions (W x D x H)		inch	35-3/8 x 13-3/8 x 52
		mm	900 x 340 x 1,345
Weight	Net	lbs/kg	246 / 112
	Gross	lbs/kg	274 / 124
Other			
Capacity Diversity Range(IDUs/ODU)		-	50%~135%
Moisture Protection		-	IPX4

R410A INVERTER ETL Intertek AHRI CERTIFIED SA

TOSOT


TMV- 5 mini Series

36,000 BTU / VRF SYSTEM

TMVRF-OD36KHP

Dimension and Installation Hole

Unit: mm(inch)



R410A INVERTER Intertek AHRI CERTIFIED

TOSOT


TMV- 5 mini Series


36,000 BTU / VRF SYSTEM

TMVRF-OD36KHP


Installation Clearance

Unit: mm(inch)





Acoustic Octave-band Sound Power Data




R410A INVERTER ETL Intertek AHRI CERTIFIED

TOSOT

TMV- 5 mini Series

36,000 BTU / VRF SYSTEM



Each Y-type branch equals to 0.5m (1-5/8ft) and each branch header equals to 1.0m (3-1/4ft).

—		Allowable value		Fitting pipe
		m	feet	
Total length (actual length) of fitting pipe		300	984	L1+L2+L3+a+b+c+d
Length of farthest fitting pipe	Actual length	120	394	L1+L2+L3+d
	Equivalent length	150	492	
From the 1st branch to the farthest indoor pipe		40	131	L2+L3+d
Height difference between ODU and IDU	ODU at upper side	50	164	—
	ODU at lower side	40	131	—
Height difference between IDUs		15	49	—

R410A INVERTER ETL Intertek AHRI CERTIFIED