TMV- 5 mini Series

60,000 BTU / VRF SYSTEM

SUBMITTAL DATA: TMVRF-OD60KHP

Job Name	Location		Date	
Purchaser	Engineer			
Submitted To	For	☐ Reference	☐ Approval	☐ Construction
Unit Designation	Schedule No.			

TMVRF-OD60KHP



Model			TMVRF-OD60KHP
System Performance			
Capacity Range		Ton	5
Nominal Capacity	Cooling	kBtu/h	60
	Heating	kBtu/h	64
Sound Pressure Level		dB(A)	63
Operating Temperature Range	Cooling	°C/°F	-5~48 / 23~118
	Heating	°C/°F	-20~27 / -4~81
AHRI Certificate Reference Number		-	212117658 / 212117660
Cooling Capacity@95F		kBtu/h	60 / 60
SEER(Ducted/Non-Ducted)		-	19.50 / 21.00
SEER2(Ducted/Non-Ducted)		-	18.00 / 20.00
Heating Capacity@47F		kBtu/h	64 / 64
HSPF(Ducted/Non-ducted)		-	10.50 / 11.00
HSPF2(Ducted/Non-ducted)		-	8.50 / 9.80
Heating Capacity@5F(Ducted/Non-ducted)		kBtu/h	31.0 / 32.0
Electrical Data			
Power Supply		-	208/230V, 1 Phase, 60Hz
Maximum Overcurrent Protection (MOP)		A	40.0
Minimum Circuit Amps (MCA)		A	34.5
Fan			
Type x Quantity		-	Axial- flow x 2
Air Flow Volume		CFM	4,590
		m^3/h	7,800
Fan Motor Power Output		W	150
Compressor			
Compressor Type x Quantity		-	Inverter rotary x 1
Compressor Rated Load Amps (RLA)		A	19.1
Oil Type		-	FV50S
Oil Charge Volume(Compressor charged)		L	1.7
Connection Piping			
Gas Pipe		inch	3/4
Liquid Pipe		inch	3/8
Refrigerant Type		-	R410A
Refrigerant Charge Amount		kg/oz	4.6 / 162.3
Dimension/Weight			
Unit Dimensions (W x D x H)		inch	37 x 12-5/8 x 56-1/4
		mm	940 x 320 x 1,430
Weight	Net	lbs/kg	273 / 124
	Gross	lbs/kg	299 / 136
Other			
Capacity Diversity Range(IDUs/ODU)		-	50%~135%
Moisture Protection		-	IPX4

TOSOT


TMV- 5 mini Series

60,000 BTU / VRF SYSTEM

TMVRF-OD60KHP

Dimension and Installation Hole

Unit: mm(inch)



R410A INVERTER ETL Intertek AHRI CERTIFIED CSA

TOSOT


TMV- 5 mini Series


60,000 BTU / VRF SYSTEM

TMVRF-OD60KHP


Installation Clearance

Unit: mm(inch)





Acoustic Octave-band Sound Power Data




R410A INVERTER Intertek AHRI CERTIFIED

TOSOT

TMV- 5 mini Series

60,000 BTU / VRF SYSTEM



Each Y-type branch equals to 0.5m (1-5/8ft) and each branch header equals to 1.0m (3-1/4ft).

—		Allowable value		Fitting pipe
		m	feet	
Total length (actual length) of fitting pipe		300	984	L1+L2+L3+a+b+c+d
Length of farthest fitting pipe	Actual length	120	394	L1+L2+L3+d
	Equivalent length	150	492	
From the 1st branch to the farthest indoor pipe		40	131	L2+L3+d
Height difference between ODU and IDU	ODU at upper side	50	164	—
	ODU at lower side	40	131	—
Height difference between IDUs		15	49	—

R410A INVERTER Intertek AHRI CERTIFIED