Single Zone System
R32 HEAT / COOL
HIGH HEAT, DAILY CHARMING, COOLING CHARMO

18,000 BTU / H WALL MOUNTED HEAT- PUMP SYSTEM

SUBMITTAL DATA: TWH18JD32AI+TWH18JD32AO

Job Name	**Location**		**Date**	
Purchaser	**Engineer**			
Submitted To	**For**	☐ **Reference**	☐ **Approval**	☐ **Construction**
Unit Designation	**Schedule No.**			

AHRI CERTIFIED REF	**218743775**
ENERGY STAR No.	**4711867**





YBE1FB1F
(Standard)



YAW1F9
Cool-only
(Optional)



XE72-44/E
(Optional)



XE71-00/E
(Optional)



SYSTEM RATINGS		INDOOR UNIT DATA	
Cooling		**Fan Motor**	
Rated Capacity at 95° F	18,000 BTU/H	Type	Cross-flow
Capacity Range	5,800-26,270 BTU/H	Output Power	50 W
		FLA	0.60 A
Power Input (Max)	2,400 W	Fan Speeds	7
Power Input (Min)	500 W	Air flow (Min/Max)	412 / 677 CFM
SEER2 / EER2	19.5 / 13.3	Drainage Hose Size	5/8”
Heating		**Sound Pressure Level**	
Rated Capacity at 47° F	18,000 BTU/H	Cooling (Low/High)	36 / 51 dB(A)
Capacity Range	5,400-26,600 BTU/H	Heating (Low/High)	36 / 51 dB(A)
Rated Capacity @ 17°F	19,600 BTU/H	**Dehumidification**	5.28 pt/hr
Rated Capacity @ 5°F	16,800 BTU/H	**OUTDOOR UNIT DATA**	
Power Input (Max)	2,600 W	**Compressor**	
Power Input (Min)	400 W	Type	DC Inverter Rotary
HSPF2 (Region IV / V)	9.0 / 7.0	RLA	10.0 A
COP @5°F	1.81	**Fan Motor**	
Operating Range		Output Power	50 W
Cooling	0°F ~ 118°F -18°C ~ 48°C	RLA	1.0 A
		Sound Pressure Level	54 dB(A)
Heating	-13°F ~ 75°F -25°C ~ 24°C	**Refrigerant Piping Data**	
		Liquid Pipe Size (OD)	1/4-in
Power Supply		Gas Pipe Size (OD)	1/2-in
Rated	208/230 V, 1 Phase, 60 Hz	Connection Method	Flared
Voltage Range	187 - 253 V	Pre-Charged R32 Amount	42.3 oz
Main Power Wire Size	Per Local Code	Additional Charge	0.1 oz/ft
Wire Size between IDU & ODU	14-4 AWG	Pre-Charge Length	25-ft
MCA	15 A	MAX Refrigerant Pipe Length	131-ft
MOCP/Max Breaker Size	20 A	MIN Refrigerant Pipe Length	10-ft
Moisture Protection	IPX4	MAX Refrigerant Pipe Height Difference	82-ft


TOSOT.COM

FEATURES & FUNCTION: TWH18JD32AI + TWH18JD32AO


SYSTEM FEATURES	
Ultra Low Frequency Torque Control	Yes
Power Factor Correction	Yes
Compressor Type	Rotary
Outdoor Unit Drain Pan / Chassis Electric Heater	YES
Indoor & Outdoor Fin Coating (Blue)	Acrylic Resin / Anti-Corrosion
Built-in Condensate Pump	NO
Memory/Power Failure Recovery	YES
Self Diagnosis	YES
WIFI Included	YES
Indoor Fan Type	Cross-flow
Multi Fan Speeds	7 Speeds
Indoor Unit Display	YES
Auxiliary Electrical Heater	NO
Auto Mode	YES
Auto Fan	YES
Dry Mode	YES
Dry Anti-Mildew Mode / X-Fan	YES
Energy Saving Mode / I-demand	YES
Dirty Filter Alert	YES
I Feel Function	YES
Child Lock on Remote Controller	YES
Quiet Mode	YES
Mini HRV/ERV Connectable	NA
Artificial Intelligence for Saving Energy	Version 1.0
Freeze Guard Mode	YES
Wireless Interlock with Sinope Thermostat	Optional
R32 Leakage Detector	Optional
Low Temperature Cooling / Heating	YES
24Vac Signal 3rd party Backup Heater Output	XE71-00/E
Auto Swing	Vertical
Intelligent Defrosting	YES
Thin Frost Rapid Removing	NO
Intelligent Dehumidify	NO
Power Gear	NO
ODU Self-Cleaning	NO
Auto Brightness for Panel Display	NO
Buzz Volume Adjustable	NO

EXTENDED RATINGS: TWH18JD32AI + TWH18JD32AO

Cooling capacity correction curve




Heating capacity correction curve




SPACING REQUIREMENT: TWH18JD32AI + TWH18JD32AO

INDOOR UNIT


Unit: inch



OUTDOOR UNIT



The ceiling should be open





Either left or right side should be open

Note: Wall height on air outlet side ≤ 50inch

DIMENSIONAL : TWH18JD32AI + TWH18JD32AO

INDOOR UNIT






Unit: inch


Dimensions	
D	9 11/16
H	13 7/64
W	42 7/16
W1	6 15/64
W2	22 7/64
W3	10 5/32


Weight (Net/Shipping)
33 / 40 LBS

Liquid Line Valve	1/4-in OD Flared
Gas Line Valve	1/2-in OD Flared
Drain Connector	5/8-in OD

OUTDOOR UNIT







Weight (Net/Shipping)
94 / 104 LBS

Liquid Line Valve	1/4-in OD Flared
Gas Line Valve	1/2-in OD Flared

Notes:
1.Recommended Interconnecting Cable Type AWG 14/4
2.Power wiring cable size must comply with applicable national and local codes
3.Test conditions are based on AHRI 210/240